



| NOMINAL AIRFLOW (CFM) | | ECM H.P | FULL LOAD AMPS 115 V | SOUND (dBA) | | UNIT WEIGHT (lbs) |
|-----------------------|-----|------------|-------------------------|-------------|---------|----------------------|
| MIN | MAX | | | 300 CFM | 550 CFM | |
| 150 | 600 | 1/3 | 4.6 | 46 | 59 | 125 |

NOTES:

- 18 GAUGE CONSTRUCTION
- WHITE POWDER COAT FINISH, 1000 HR SALT SPRAY RATED
- VARIABLE SPEED EC MOTOR, 60 CYCLE
- 115V POWER CORD
- FAN ON/OFF SWITCH
- EXTERNAL FAN ADJUSTMENT
- CASTERS SHIP LOOSE
- ASSEMBLY LISTED UNDER UL507/CSA 22.2 No.113 & UL867/CSA 22.2 No.187
- BIPOLAR IONIZER MEETS UL 2998

OPTIONS:

- UV LIGHT
- BIPOLAR IONIZATION
- BIPOLAR IONIZATION & UV LIGHT



ALL METRIC DIMENSIONS () ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

| | | | |
|------------------------|----------------------|---------------|-----------------------------------------------------------------------|
| PROJECT: | | PRICE | |
| ENGINEER: | | | |
| CUSTOMER: | | 272458 | RAP ROOM AIR PURIFIER 600 CFM HEPA RECIRCULATION UNIT |
| SUBMITTAL DATE: | SPEC. SYMBOL: | 2020/09/01 | |